Apparent Simazine 900 WG Herbicide

AIRR Apparent Pty Ltd.

Chemwatch Hazard Alert Code: **2**

Chemwatch: **9656-54**
Version No: **2.1**
Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Initial Date: **06/11/2026**
Revision Date: **06/11/2026**
Print Date: **23/11/2026**
L.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Apparent Simazine 900 WG Herbicide
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains simazine)
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	A selective agricultural water dispersible granule herbicide. Use according to manufacturer's directions.

Details of the manufacturer or importer of the safety data sheet

Registered company name	**AIRR Apparent Pty Ltd.**
Address	15/16 Princes Street, Newport NSW 2106 Australia
Telephone	+61 3 5820 8400
Fax	Not Available
Website	www.apparent.com.au
Email	enquiries@apparentag.com.au

Emergency telephone number

Association / Organisation	**AIRR Apparent Pty Ltd.**
Emergency telephone number(s)	1800 033 111 (24 Hours)
Other emergency telephone number(s)	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification [1]	Acute Toxicity (Oral) Category 4, Serious Eye Damage/Eye Irritation Category 2B, Carcinogenicity Category 2, Specific Target Organ Toxicity - Repeated Exposure Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 1
Legend:	***1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI***

Label elements

Hazard pictogram(s)	
Signal word	**Warning**

Hazard statement(s)

Page 1 continued...

H302	Harmful if swallowed.
H320	Causes eye irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statement(s) Prevention

P260	Do not breathe dust/fume.
P280	Wear protective gloves and protective clothing.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P202	Do not handle until all safety precautions have been read and understood.

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P330	Rinse mouth.

Precautionary statement(s) Storage

P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
122-34-9	90	simazine
Not Available	balance	Ingredients determined not to be hazardous
Legend:	***1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available***	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: ▸ Wash out immediately with fresh running water. ▸ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▸ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ▸ Immediately remove all contaminated clothing, including footwear. ▸ Flush skin and hair with running water (and soap if available). ▸ Seek medical attention in event of irritation.
Inhalation	▸ If fumes or combustion products are inhaled remove from contaminated area. ▸ Lay patient down. Keep warm and rested. ▸ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▸ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▸ Transport to hospital, or doctor, without delay.
Ingestion	▸ **IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.** ▸ For advice, contact a Poisons Information Centre or a doctor. ▸ Urgent hospital treatment is likely to be needed. ▸ In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. ▸ If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. ▸ If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.

Continued...

Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:
- **INDUCE** vomiting with fingers down the back of the throat, **ONLY IF CONSCIOUS**. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
For triazines:
Clinical effects:
Nausea, vomiting, diarrhoea, abdominal pain and a burning sensation in the mouth.However, due to the lack of clinical data serious effects cannot be excluded from large dose deliberate ingestions.
In the case of products with organic solvents, aspiration can develop. Ataxia, anorexia, dyspnoea and muscle spasms have all been reported in animal studies but have not been seen in humans.
Management principles:
Ingestion:
- In most cases there is probably no need for anything other than oral fluids and reassurance. If a very large amount has been ingested then consider: adult: gastric lavage (with a cuffed endotracheal tube if an organic solvent is involved) followed by 50 g activated charcoal, child: 1 g/kg activated charcoal.
- Do not induce vomiting if product contains an organic solvent.
- Observe the patient if a large dose has been ingested.
- Symptomatic and supportive care.

Inhalation:
- Remove to fresh air. Give oxygen if necessary.
- Bronchodilators may be given if indicated. Otherwise treat for the particular solvent involved.

Skin:
- Wash with copious amounts of water and prevent drying/cracking (due to solvent) with an emollient

Eye:
- Irrigate for 15 to 20 minutes with running water or saline.
- Refer to an ophthalmologist.

IPCS InChem Series

SECTION 5 Firefighting measures

Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

Special hazards arising from the substance or mixture

Fire Incompatibility	‣ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting	‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ Wear breathing apparatus plus protective gloves. ‣ Prevent, by any means available, spillage from entering drains or water courses. ‣ Use water delivered as a fine spray to control fire and cool adjacent area. ‣ **DO NOT** approach containers suspected to be hot. ‣ Cool fire exposed containers with water spray from a protected location. ‣ If safe to do so, remove containers from path of fire. ‣ Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	‣ Combustible solid which burns but propagates flame with difficulty; it is estimated that most organic dusts are combustible (circa 70%) - according to the circumstances under which the combustion process occurs, such materials may cause fires and / or dust explosions. ‣ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions). ‣ Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited - particles exceeding this limit will generally not form flammable dust clouds; once initiated, however, larger particles up to 1400 microns diameter will contribute to the propagation of an explosion. ‣ In the same way as gases and vapours, dusts in the form of a cloud are only ignitable over a range of concentrations; in principle, the concepts of lower explosive limit (LEL) and upper explosive limit (UEL) are applicable to dust clouds but only the LEL is of practical use; - this is because of the inherent difficulty of achieving homogeneous dust clouds at high temperatures (for dusts the LEL is often called the "Minimum Explosible Concentration", MEC). ‣ When processed with flammable liquids/vapors/mists,ignitable (hybrid) mixtures may be formed with combustible dusts. Ignitable mixtures will increase the rate of explosion pressure rise and the Minimum Ignition Energy (the minimum amount of energy required to ignite dust clouds - MIE) will be lower than the pure dust in air mixture. The Lower Explosive Limit (LEL) of the vapour/dust mixture will be lower than the individual LELs for the vapors/mists or dusts. ‣ A dust explosion may release of large quantities of gaseous products; this in turn creates a subsequent pressure rise of explosive force capable of damaging plant and buildings and injuring people. ‣ Usually the initial or primary explosion takes place in a confined space such as plant or machinery, and can be of sufficient force to damage or rupture the plant. If the shock wave from the primary explosion enters the surrounding area, it will disturb any settled dust layers, forming a second dust cloud, and often initiate a much larger secondary explosion. All large scale explosions have resulted from chain reactions of this type. ‣ Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport. ‣ Build-up of electrostatic charge may be prevented by bonding and grounding. ‣ Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting. ‣ All movable parts coming in contact with this material should have a speed of less than 1-meter/sec.

Continued...

	▸ A sudden release of statically charged materials from storage or process equipment, particularly at elevated temperatures and/ or pressure, may result in ignition especially in the absence of an apparent ignition source. ▸ One important effect of the particulate nature of powders is that the surface area and surface structure (and often moisture content) can vary widely from sample to sample, depending of how the powder was manufactured and handled; this means that it is virtually impossible to use flammability data published in the literature for dusts (in contrast to that published for gases and vapours). ▸ Autoignition temperatures are often quoted for dust clouds (minimum ignition temperature (MIT)) and dust layers (layer ignition temperature (LIT)); LIT generally falls as the thickness of the layer increases. Combustion products include: ▸ carbon monoxide (CO) ▸ carbon dioxide (CO_2) hydrogen chloride phosgene nitrogen oxides (NOx) ▸ other pyrolysis products typical of burning organic material.
HAZCHEM	2Z

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	▸ Clean up waste regularly and abnormal spills immediately. ▸ Avoid breathing dust and contact with skin and eyes. ▸ Wear protective clothing, gloves, safety glasses and dust respirator. ▸ Use dry clean up procedures and avoid generating dust. ▸ Vacuum up or sweep up. **NOTE:** Vacuum cleaner must be fitted with an exhaust micro filter (H-Class HEPA type) (consider explosion-proof machines designed to be grounded during storage and use). H-Class HEPA filtered industrial vacuum cleaners should NOT be used on wet materials or surfaces. ▸ Dampen with water to prevent dusting before sweeping. ▸ Place in suitable containers for disposal. Environmental hazard - contain spillage.
Major Spills	Environmental hazard - contain spillage. Moderate hazard. ▸ **CAUTION**: Advise personnel in area. ▸ Alert Emergency Services and tell them location and nature of hazard. ▸ Control personal contact by wearing protective clothing. ▸ Prevent, by any means available, spillage from entering drains or water courses. ▸ Recover product wherever possible. ▸ **IF DRY:** Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. **IF WET:** Vacuum/shovel up and place in labelled containers for disposal. ▸ **ALWAYS:** Wash area down with large amounts of water and prevent runoff into drains. ▸ If contamination of drains or waterways occurs, advise Emergency Services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▸ Avoid skin contact, including inhalation. ▸ Wear protective clothing when risk of exposure occurs. ▸ Use in a well-ventilated area. ▸ Prevent concentration in hollows and sumps. ▸ **DO NOT** enter confined spaces until atmosphere has been checked. ▸ **DO NOT** allow material to come in direct contact with human skin or eyes. ▸ **DO NOT** allow material to come in contact with exposed food or food contact surfaces. ▸ Suitable PPE must be worn at all times. ▸ Avoid contact with incompatible materials. ▸ When handling, **DO NOT** eat, drink or smoke. ▸ Keep containers securely sealed when not in use. ▸ Avoid physical damage to containers. ▸ Always wash hands with soap and water after handling. ▸ Work clothes should be laundered separately. Launder contaminated clothing before re-use. ▸ Use good occupational work practice. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS. ▸ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. ▸ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions) ▸ Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. ▸ Establish good housekeeping practices. ▸ Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds. ▸ Use continuous suction at points of dust generation to capture and minimise the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimise the probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area. ▸ Do not use air hoses for cleaning. ▸ Minimise dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Vacuums with explosion-proof motors should be used. ▸ Control sources of static electricity. Dusts or their packages may accumulate static charges, and static discharge can be a source of ignition. ▸ Solids handling systems must be designed in accordance with applicable standards (e.g. NFPA including 654 and 77) and other national guidance. ▸ Do not empty directly into flammable solvents or in the presence of flammable vapors.

Continued...

	▸ The operator, the packaging container and all equipment must be grounded with electrical bonding and grounding systems. Plastic bags and plastics cannot be grounded, and antistatic bags do not completely protect against development of static charges. Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source. ▸ Do NOT cut, drill, grind or weld such containers. ▸ In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.
Other information	▸ Store in original containers. ▸ Keep containers securely sealed. ▸ Store in a cool, dry area protected from environmental extremes. ▸ Store away from incompatible materials and foodstuff containers. ▸ Protect containers against physical damage and check regularly for leaks. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS. For major quantities: ▸ Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams}. ▸ Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.

Conditions for safe storage, including any incompatibilities

Suitable container	**DO NOT** repack. Use only containers as originally supplied by manufacturer ▸ Polyethylene or polypropylene container. ▸ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Contains a six-membered heterocyclic ring. Six-membered heterocycles can be described as pi--deficient. Substitution by electronegative groups or additional nitrogen atoms in the ring significantly increase the pi-deficiency. These effects also decrease the basicity. Electrophilic aromatic substitution is more difficult while nucleophilic aromatic substitution is facilitated. Although triazines are aromatic compounds, their resonance energy is much lower than in benzene. Electrophilic aromatic substitution is difficult - nucleophilic aromatic substitution is easier. The 1,2,4-triazines can react with electron-rich dienophiles in an inverse electron demand Diels-Alder reaction. This forms a bicyclic intermediate which normally then extrudes a molecule of nitrogen gas to form an aromatic ring again. In this way the 1,2,4-triazines can be reacted with alkynes to form pyridine rings. Triazine-based ligands have been used to bind three dinuclear arene ruthenium (or osmium) compounds to form metallaprisms. ▸ Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

MATERIAL DATA

It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.
At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.
NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.
Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.
OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. ▸ Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. ▸ Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace. ▸ If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks ▸ Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding. ▸ Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

Continued...

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.

Type of Contaminant:	Air Speed:
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 ft/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 ft/min)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 ft/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment



Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection

See Hand protection below

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:
· frequency and duration of contact,
· chemical resistance of glove material,
· glove thickness and
· dexterity
Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).
· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
· Contaminated gloves should be replaced.
As defined in ASTM F-739-96 in any application, gloves are rated as:
· Excellent when breakthrough time > 480 min
· Good when breakthrough time > 20 min
· Fair when breakthrough time < 20 min
· Poor when glove material degrades
For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.
It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential
Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene.
- nitrile rubber.
- butyl rubber.
- fluorocaoutchouc.
- polyvinyl chloride.

Gloves should be examined for wear and/ or degradation constantly.

Body protection

See Other protection below

Other protection

- Overalls.

Continued...

	‣ P.V.C apron. ‣ Barrier cream. ‣ Skin cleansing cream. ‣ Eye wash unit.

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	- -	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow
A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
· The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
· Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
· Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
· Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
· Use approved positive flow mask if significant quantities of dust becomes airborne.
· Try to avoid creating dust conditions.
Class P2 particulate filters are used for protection against mechanically and thermally generated particulates or both.
P2 is a respiratory filter rating under various international standards, Filters at least 94% of airborne particles
Suitable for:
· Relatively small particles generated by mechanical processes eg. grinding, cutting, sanding, drilling, sawing.
· Sub-micron thermally generated particles e.g. welding fumes, fertilizer and bushfire smoke.
· Biologically active airborne particles under specified infection control applications e.g. viruses, bacteria, COVID-19, SARS

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Whitish coloured granule.

Physical state	Divided Solid	**Relative density (Water = 1)**	Not Available
Odour	Slight	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Available
pH (as supplied)	Not Available	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	Not Available	**Viscosity (mm2/s)**	Not Available
Initial boiling point and boiling range (°C)	Not Available	**Molecular weight (g/mol)**	Not Applicable
Flash point (°C)	Not Available	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	Not Applicable	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	Not Available	**Surface Tension (dyn/cm or mN/m)**	Not Applicable
Lower Explosive Limit (%)	Not Available	**Volatile Component (%vol)**	Not Available
Vapour pressure (kPa)	Not Available	**Gas group**	Not Available
Solubility in water	Partly miscible	**pH as a solution (1%)**	Not Available
Vapour density (Air = 1)	Not Available	**VOC g/L**	Not Available
Heat of Combustion (kJ/g)	Not Available	**Ignition Distance (cm)**	Not Available
Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	‣ Unstable in the presence of incompatible materials. ‣ Product is considered stable. ‣ Hazardous polymerisation will not occur.

Continued...

Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	There is sufficient evidence to classify this material as acutely toxic.
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	There is sufficient evidence to classify this material as carcinogenic
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	Based on available data, the classification criteria are not met.
i) STOT - Repeated Exposure	There is sufficient evidence to classify this material as toxic to specific organs through repeated exposure
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures. Not normally a hazard due to non-volatile nature of product
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Short-term administration of derivatives of s-triazines cause structural damage to the liver of test animals. The significance of these results (if any) for human exposure cannot, as yet, be determined. [Foltinova etal - Folia Histochemica 1971]. The s-triazines appear to act at the level of carbohydrate metabolism. The chlorinated, methoxy and methylthio derivatives inhibit starch accumulation by blocking sugar production. The s-triazines also cause the disappearance of sucrose and glyceric acid with the formation of aspartic and malic acids.
Skin Contact	The material produces mild skin irritation; evidence exists, or practical experience predicts, that the material either ‣ produces mild inflammation of the skin in a substantial number of individuals following direct contact, and/or ‣ produces significant, but mild, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by a temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.
Chronic	On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment. Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces severe lesions. Such damage may become apparent following direct application in subchronic (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity tests. Exposure to the material may cause concerns for human fertility, generally on the basis that results in animal studies provide sufficient evidence to cause a strong suspicion of impaired fertility in the absence of toxic effects, or evidence of impaired fertility occurring at around the same dose levels as other toxic effects, but which are not a secondary non-specific consequence of other toxic effects. Exposure to the material may cause concerns for humans owing to possible developmental toxic effects, generally on the basis that results in appropriate animal studies provide strong suspicion of developmental toxicity in the absence of signs of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not a secondary non-specific consequence of other toxic effects. Epidemiological studies have associated long-term exposures to triazine herbicides with increase risk of ovarian cancer in female farm workers in Italy and of breast cancer in the general population of Kentucky in the United States. In experiments with female F344 rats, atrazine induced tumours of the mammary gland and reproductive organs. Atrazine also caused lengthening of the oestrus cycle, a dose-dependent increase in the plasma levels of 17beta-oestradiol and early onset of mammary and pituitary tumours in female Prague-Dawley rats. Investigations into the mechanism of these apparent oestrogenic effects have not been able to demonstrate any consistent interactions with triazine herbicides with the oestrogen receptor or effects on receptor-mediated responses. Atrazine, simazine and propazine have been

Continued...

	shown to induce aromatase activity in a human adrenocortical carcinoma cell line. This response was observed at concentrations in the submicromolar range. Aromatase is a circulating enzyme which converts androstenedione (generated in the adrenals) to oestrone in peripheral tissues such as adipose tissues. Oestrone subsequently undergoes conversion to oestradiol which binds to oestrogen receptors in many tissues with induction of tumours. In addition, many human breast cancers contain aromatase. (Breast cancer therapies, based on aromatase inhibitors, are now available.) The effects of triazine herbicides and some of their metabolites on aromatase activity may provide a partial explanation for the observed increase in plasma oestradiol in rats, together with the observed oestrogen-mediated toxicities ***in vivo. [1]*** ***[1] Sanderson et al: Environmental Health Perspectives, 109, pp 1027-1031, 2001*** Suggestive evidence between atrazine (or triazines) exposure and an increased risk of prostate cancer, breast cancer, and ovarian cancer have been reported. Although these data provide a suspicion of carcinogenicity, the limited number of investigations and study limitations preclude drawing conclusions regarding these cancer types. Long term exposure to high dust concentrations may cause changes in lung function (i.e. pneumoconiosis) caused by particles less than 0.5 micron penetrating and remaining in the lung. A prime symptom is breathlessness. Lung shadows show on X-ray. Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.

Apparent Simazine 900 WG Herbicide	**TOXICITY**	**IRRITATION**
	Not Available	Not Available
simazine	**TOXICITY**	**IRRITATION**
	dermal (rat) LD50: >2000 mg/kg[1]	Eye (Rodent - rabbit): 80mg - Moderate
	Inhalation (Rat) LC50: >2.21 mg/l4h[1]	Skin (Rodent - rabbit): 500mg - Mild
	Oral (Rat) LD50: 971 mg/kg[2]	

Legend:	***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***

Apparent Simazine 900 WG Herbicide	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.
SIMAZINE	NOEL (2 years): for rats 100 mg/kg diet (7 mg/kg daily); for dogs 150 mg/kg diet (5 mg/kg daily) NOTE: Chronic feeding studies of simazine (technical) on female rats resulted in an increase in the incidence of mammary tumours. This result could not be duplicated in mice or male rats. ADI: 0.005 mg/kg/day NOEL: 0.5 mg/kg/day ***[* The Pesticides Manual, Incorporating The Agrochemicals Handbook, 10th Edition, Editor Clive Tomlin, 1994, British Crop Protection Council]***
Apparent Simazine 900 WG Herbicide & SIMAZINE	The substance is classified by IARC as Group 3: **NOT** classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Acute Toxicity	✔	**Carcinogenicity**	✔
Skin Irritation/Corrosion	✘	**Reproductivity**	✘
Serious Eye Damage/Irritation	✔	**STOT - Single Exposure**	✘
Respiratory or Skin sensitisation	✘	**STOT - Repeated Exposure**	✔
Mutagenicity	✘	**Aspiration Hazard**	✘

Legend: ✘ ***– Data either not available or does not fill the criteria for classification***
✔ ***– Data available to make classification***

SECTION 12 Ecological information

Toxicity

Apparent Simazine 900 WG Herbicide	**Endpoint**	**Test Duration (hr)**	**Species**	**Value**	**Source**
	Not Available	Not Available	Not Available	Not Available	Not Available

simazine	**Endpoint**	**Test Duration (hr)**	**Species**	**Value**	**Source**
	EC50	72h	Algae or other aquatic plants	0.047-0.064mg/L	4
	BCF	1008h	Fish	2.3-3.2	7
	EC50	48h	Crustacea	0.728-2.86mg/L	4
	EC50(ECx)	336h	Algae or other aquatic plants	<0.001mg/L	4
	EC50	96h	Algae or other aquatic plants	0.082mg/l	4
	LC50	96h	Fish	0.17-0.36mg/L	4

Continued...

Legend:	***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data 8. User defined data***

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.
Wastes resulting from use of the product must be disposed of on site or at approved waste sites.
The triazine pesticides behave as weak bases in aqueous solution. Triazines are more soluble at low pHs. Adsorption of triazines through an exchange process to organic matter and clay minerals is dependent on the pH of the solution and the acidity of the absorbent surface. Hydrogen bonding and hydrophobic bonding also occur with soil organic matter at higher pHs. Hydrolysis and oxidation are general routes of soil metabolism whilst photodecomposition appears to be minimal. Vapour transport losses are dependent on vapour pressure and the pH of the evaporating surface as ionised compounds are less volatile. Transport from soil to water occurs in solution and in sediments. Herbicide concentrations in excess of 5 ppb may play a part in the decline in submerged aquatic vegetation (SAV). However, recovery from exposure to these concentrations does occur as these herbicides degrade rapidly under estuarine conditions. Residues do not appear to build up in sediments.
for simazine:
Kow 91.2
Bioaccumulation : not significant
No significant biological degradation.
Occurrence in Air The potential for simazine to volatilise from a soil and water system is low as indicated by its low vapor pressure (6.1 x 10-9 mm Hg) and Henry s constant (9.48 x 10-10 atm-m3.mole). The vertical fluxes of simazine were measured by air-sampling and aerodynamic measurement, over 24 days, after surface application of the compound on a fallow soil. Calculated volatilisation losses of simazine in the first 21 days were 0.021 kg/ha of 1.68 kg of a.i./ha (1.3% loss). Daily losses depended on moisture content because simazine, applied as a wettable powder, became susceptible to wind erosion as the soil surface dried in the noontime solar radiation. However, the volatilization losses were much smaller than dissipation by chemical degradation but equivalent to reported surface runoff concentrations.
Biotic degradation: The aerobic and anaerobic degradation half-life values (respectively 91 days, 70-77 days, sandy loam) indicate that simazine is persistent in the environment (up to eight months) and not easily degraded by microbes. However, biotic degradation seems to be the most effective method of simazine degradation compared to the abiotic processes. A gram-positive bacterium, ***Arthrobacter aurescens*** strain TC1, is capable of consuming 3000 mg/L of atrazine in liquid as a sole carbon and nitrogen source via catabolism to supplement its growth. This bacterium is also capable of degrading 23 other s-triazines, including simazine. In addition to bacterium capable of degrading simazine, fungal strains have been identified as well. ***Penicillium steckii*** gradually degraded 50 mg/L of simazine in a 25 mg/L yeast extract. The fungal strain can grow with simazine as its sole carbon and nitrogen source.
Soil: A major concern with any agricultural pesticide is its potential to leach from the soil to surface or ground water systems that are used as drinking water sources. The sorption and desorption of simazine in soils play a fundamental role in the prevention of contamination of water, which in turn is affected by the heterogeneous nature of soil systems having different soil types and amounts of organic matter (OM). A study on simazine sorption onto hydroxyl aluminum coated and uncoated montmorillonite (hydrated silicate hydroxide containing sodium, calcium, aluminum, and magnesium) was conducted. Simazine was adsorbed more to clays at low pH (3.7) and uncoated clay surfaces (Koc = 458), whereas simazine sorption to hydroxyl aluminum coated montmorillonite was reduced (Koc = 16).
Desorption experiments showed that very little simazine was desorbed from the montmorillonite clay surface indicating strong electrostatic interactions (low concentration of simazine).
In a similar study it is reported that montmorillonite is the main mineral soil colloid contributing to simazine sorption and in contrast, ferrihydrite, an iron oxide mineral, does not sorb simazine. It was also reported that when hydrophobic processes are not dominant, interactions and competition for sorption sites between simazine and water molecules can take place. Soil moisture has been shown in many studies to contribute to the sorption and dissipation of simazine. A relationship was shown to exist between the temperature and residue of herbicides in soil and also a positive tendency was observed between soil moisture content and degradation; higher temperature and moisture content lead to faster degradation of simazine
Water: Simazine as a contaminant in water systems is of primary importance because ground and surface waters are used in many communities as the primary source of drinking water. Simazine, and its degradation products (deisopropyl atrazine and diamino chlorotriazine) has been shown to reach both surface and ground waters and in some cases approach the U.S. MCL of 4 ug/L
Reactivity: Simazine can be dechlorinated when the compound is heated with caustic alkalies under laboratory conditions In environmental systems, the same dechlorination process and subsequent hydrolysis may take place under high pH conditions . The resulting compound is 2-hydroxy-4,6-bis(ethlyamino)-s-triazine. Interestingly, this compound does not have herbicidal properties.
Simazine can also loose an alkyl group and the subsequent product, deisopropyl atrazine has been detected in groundwater. Photochemical degradation has been found by to lead to alkyl group loss and subsequent production of deisopropyl atrazine and diamino chlorotriazine.
No appreciable degradation of simazine occurred over a period of 100 days at 15 C in the dark at pH 7 and 9. However, a half-life (t1/2) of 145 days was calculated for the degradation of simazine at pH 4.0 (lowest pH that would be found in aquatic environments) in the dark indicating that hydrolysis reactions occur at a slow rate. The presence of 70 mg/L dissolved organic matter (DOM) had no catalytic effect on the transformation of simazine at pH 8.0 and 40 C.
The acid-catalyzed hydrolysis of simazine has been examined; Calculations indicate that the enthalpy of hydrolysis (delta.hH), Gibbs free energy of hydrolysis (delta.hG), and entropy of hydrolysis (delta.hS) at 25 C are -70, -63, and -23 kJ/mol, respectively. Such a delta.hG value indicates the hydrolysis is energetically spontaneous but this was not observed in many studies. Hydrolysis of simazine appears to be kinetically controlled.
Photolysis: Among the abiotic reactions that may take place in regards to simazine degradation, photochemical reactions play a major role. The photolytic degradation t1/2 for simazine ranged from 4.5-21 days. The degradation of simazine in natural waters using UV radiation (lambda >290 nm) has been examined; in the dark, there was no degradation of simazine in water from three sources (distilled, lake, and river waters). Therefore, hydrolytic processes do not seem to play a significant role in simazine decomposition. Simazine readily degraded in water under UV radiation, however. The t1/2 for simazine was calculated to be between 2.7 and 5.4 hours depending on the source of water and other factors such as oxygen content and organic matter (OM) content in the waters. Degradation followed first-order curves. Hydrogen peroxide addition to water significantly enhanced simazine degradation (up to four times faster degradation). Two degradative pathways are proposed ; one involving the dechlorination and subsequent hydroxy substitution of the ring and the other involves the oxidation of the propyl side chains on simazine. The main photochemical degradation products from simazine were found to be 2-hydroxy-4,6-bis(ethylamino)-s-triazine, 2-chloro-4-amino-6-ethylamino)-s-triazine (deisopropylatrazine), and 2-chloro-4,6-diamino-s-triazine (diamino chlorotriazine).
Remediation: Simazine (2.5x10-5 M) can be oxidized from ozone (ozonation) by using catalytic amounts of Mn (II) (concentration = 0.1-1 mg/L) and Fe (II) (concentration = 1 to 5 mg/L). The pH was found to be a significant player in the ozonation of simazine using Mn and Fe; an increase of simazine conversion was observed as the pH was raised from 5 to 9. The main simazine ozonation byproduct was deisopropyl atrazine. Since reactivity of simazine with molecular ozone is low, decomposition of ozone to produce highly reactive species is needed. Thus, small amounts of Mn (II) added to the reaction would facilitate the degradation of simazine. The positive effects of pH (simazine degradation increases with increased pH) can be attributed to the presence of significant amounts of hydroxy ions in solution, which gives way to the non-catalytic decomposition of ozone into free hydroxyl radical ions responsible for simazine degradation
Ecotoxicity:
Practically non-toxic to birds and honeybees. Algae are sensitive to simazine in concentrations at or below the U.S. MCL (4 ug/L) whereas fish and higher order animal are more tolerant to the compound.
Daphnia magna LC50 (48 h): 1 mg/l
Algae EC50 Chlorococcum 2.5 ug/L; Dunaliella tertiolecta 4.0 ug/L; Isochrysis galbana 0.6 ug/L; Phaeodactylum tricornutum 0.5 (all show 50% decrease in growth)
Fish LC50 (96 h): bluegill sunfish >100 mg/L; rainbow trout 2.8 mg/L; fathead minnow 6.4 mg/L: (48 h): bluegill sunfish 130 mg/L
Oyster LC50 (96 h): >3.7 mg/L
Avian acute LD50: bobwhite quail 1785 mg/kg; mallard duck >10000 mg/kg
Chronic dietary LC50 (8 d): bobwhite quail 11000 mg/kg; mallard duck >5000 mg/kg
Earthworm LC50 >1000 mg/kg (in soil)
Even though the solubility of simazine in water is low (6.2 mg/L), organisms in water may have greater exposure than organisms in soil because OM in soil may sorb simazine and prevent the compound s release. Further, water suspended DOM may also limit the exposure of microbes and higher order organisms, such as fish, given simazine s low but important affinity to organic constituents. Simazine in stable submerged soils has been found to sorb beyond the top few mm of the soil. Blackfly silk and snail pedal mucus have been shown to have sorption affinities for simazine that are orders of magnitude greater than soil.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
simazine	HIGH	HIGH

Continued...

Bioaccumulative potential

Ingredient	Bioaccumulation
simazine	LOW (BCF = 14.6)

Mobility in soil

Ingredient	Mobility
simazine	LOW (Log KOC = 149)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	▸ Containers may still present a chemical hazard/ danger when empty. ▸ Return to supplier for reuse/ recycling if possible. Otherwise: ▸ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. ▸ Where possible retain label warnings and SDS and observe all notices pertaining to the product. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: ▸ Reduction ▸ Reuse ▸ Recycling ▸ Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted. ▸ **DO NOT** allow wash water from cleaning or process equipment to enter drains. ▸ It may be necessary to collect all wash water for treatment before disposal. ▸ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▸ Where in doubt contact the responsible authority.

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	
HAZCHEM	2Z

Land transport (ADG)

14.1. **UN number or ID number**	3077
14.2. **UN proper shipping name**	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains simazine)
14.3. **Transport hazard class(es)**	Class: 9 Subsidiary Hazard: Not Applicable
14.4. **Packing group**	III
14.5. **Environmental hazard**	Environmentally hazardous
14.6. **Special precautions for user**	Special provisions: 274 331 335 375 AU01 Limited quantity: 5 kg

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082
are not subject to this Code when transported by road or rail in;
(a) packagings;
(b) IBCs; or
(c) any other receptacle not exceeding 500 kg(L).
- Australian Special Provisions (SP AU01) - ADG Code 7th Ed.

Air transport (ICAO-IATA / DGR)

14.1. **UN number**	3077
14.2. **UN proper shipping name**	Environmentally hazardous substance, solid, n.o.s. (contains simazine)
14.3. **Transport hazard class(es)**	ICAO/IATA Class: 9

Continued...

ICAO / IATA Subsidiary Hazard	Not Applicable
ERG Code	9L

14.4. **Packing group**	III
14.5. **Environmental hazard**	Environmentally hazardous

14.6. **Special precautions for user**

Special provisions	A97 A158 A179 A197 A215
Cargo Only Packing Instructions	956
Cargo Only Maximum Qty / Pack	400 kg
Passenger and Cargo Packing Instructions	956
Passenger and Cargo Maximum Qty / Pack	400 kg
Passenger and Cargo Limited Quantity Packing Instructions	Y956
Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

14.1. **UN number**	3077
14.2. **UN proper shipping name**	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains simazine)

14.3. **Transport hazard class(es)**

IMDG Class	9
IMDG Subsidiary Hazard	Not Applicable

14.4. **Packing group**	III
14.5 **Environmental hazard**	Marine Pollutant

14.6. **Special precautions for user**

EMS Number	F-A, S-F
Special provisions	274 335 375 966 967 969
Limited Quantities	5 kg

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
simazine	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
simazine	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

simazine is found on the following regulatory lists

Australia Chemicals with non-industrial uses removed from the Australian Inventory of Chemical Substances (old Inventory)
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Chemical Footprint Project - Chemicals of High Concern List
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic
International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	No (simazine)
Canada - NDSL	Yes
China - IECSC	Yes
Colombia - Colombia National Industrial Chemicals Inventory	No (simazine)
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes

Continued...

National Inventory	Status
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	No (simazine)
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	No (simazine)
UAE - Control List (Banned/Restricted Substances)	Yes
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 Other information

Revision Date	06/11/2026
Initial Date	06/11/2026

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC—TWA: Permissible Concentration-Time Weighted Average
- PC—STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit。
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code

- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.
Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.
TEL (+61 3) 9572 4700.

end of SDS