Apparent Spray Grade Ammonium Sulphate 980 Herbicide Adjuvant

AIRR Apparent Pty Ltd.

Chemwatch Hazard Alert Code: **3**

Chemwatch: **9656-56**
Version No: **2.1**
Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Initial Date: **06/11/2026**
Revision Date: **06/11/2026**
Print Date: **23/11/2026**
L.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Apparent Spray Grade Ammonium Sulphate 980 Herbicide Adjuvant
Chemical Name	ammonium sulfate
Synonyms	Not Available
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	A spray grade liquid herbicide adjuvant. Use according to manufacturer's directions.

Details of the manufacturer or importer of the safety data sheet

Registered company name	**AIRR Apparent Pty Ltd.**
Address	15/16 Princes Street, Newport NSW 2106 Australia
Telephone	+61 3 5820 8400
Fax	Not Available
Website	www.apparent.com.au
Email	enquiries@apparentag.com.au

Emergency telephone number

Association / Organisation	**AIRR Apparent Pty Ltd.**
Emergency telephone number(s)	1800 033 111 (24 Hours)
Other emergency telephone number(s)	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification [1]	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 1, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Hazardous to the Aquatic Environment Acute Hazard Category 3
Legend:	***1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI***

Label elements

Hazard pictogram(s)	
Signal word	**Danger**

Hazard statement(s)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H402	Harmful to aquatic life.

Page 1 continued...

Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing dust/fumes.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7783-20-2	98-100	ammonium sulfate
Legend:	***1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available***	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: ▸ Immediately hold eyelids apart and flush the eye continuously with running water. ▸ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▸ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▸ Transport to hospital or doctor without delay. ▸ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ▸ Immediately remove all contaminated clothing, including footwear. ▸ Flush skin and hair with running water (and soap if available). ▸ Seek medical attention in event of irritation.
Inhalation	▸ If fumes or combustion products are inhaled remove from contaminated area. ▸ Lay patient down. Keep warm and rested. ▸ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▸ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▸ Transport to hospital, or doctor, without delay.
Ingestion	▸ **IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.** ▸ For advice, contact a Poisons Information Centre or a doctor. ▸ Urgent hospital treatment is likely to be needed. ▸ In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. ▸ If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. ▸ If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS. **Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:** ▸ **INDUCE** vomiting with fingers down the back of the throat, **ONLY IF CONSCIOUS**. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. **NOTE:** Wear a protective glove when inducing vomiting by mechanical means.

Continued...

Indication of any immediate medical attention and special treatment needed

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).
For poisons (where specific treatment regime is absent):

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- **DO NOT** use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.
EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994
Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substance or mixture

Fire Incompatibility	‣ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Fire Fighting	‣ Alert Fire Brigade and tell them location and nature of hazard. ‣ Wear breathing apparatus plus protective gloves. ‣ Prevent, by any means available, spillage from entering drains or water courses. ‣ Use water delivered as a fine spray to control fire and cool adjacent area. ‣ **DO NOT** approach containers suspected to be hot. ‣ Cool fire exposed containers with water spray from a protected location. ‣ If safe to do so, remove containers from path of fire. ‣ Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	‣ Combustible solid which burns but propagates flame with difficulty; it is estimated that most organic dusts are combustible (circa 70%) - according to the circumstances under which the combustion process occurs, such materials may cause fires and / or dust explosions. ‣ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions). ‣ Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited - particles exceeding this limit will generally not form flammable dust clouds; once initiated, however, larger particles up to 1400 microns diameter will contribute to the propagation of an explosion. ‣ In the same way as gases and vapours, dusts in the form of a cloud are only ignitable over a range of concentrations; in principle, the concepts of lower explosive limit (LEL) and upper explosive limit (UEL) are applicable to dust clouds but only the LEL is of practical use; - this is because of the inherent difficulty of achieving homogeneous dust clouds at high temperatures (for dusts the LEL is often called the "Minimum Explosible Concentration", MEC). ‣ When processed with flammable liquids/vapors/mists,ignitable (hybrid) mixtures may be formed with combustible dusts. Ignitable mixtures will increase the rate of explosion pressure rise and the Minimum Ignition Energy (the minimum amount of energy required to ignite dust clouds - MIE) will be lower than the pure dust in air mixture. The Lower Explosive Limit (LEL) of the vapour/dust mixture will be lower than the individual LELs for the vapors/mists or dusts. ‣ A dust explosion may release of large quantities of gaseous products; this in turn creates a subsequent pressure rise of explosive force capable of damaging plant and buildings and injuring people. ‣ Usually the initial or primary explosion takes place in a confined space such as plant or machinery, and can be of sufficient force to damage or rupture the plant. If the shock wave from the primary explosion enters the surrounding area, it will disturb any settled dust layers, forming a second dust cloud, and often initiate a much larger secondary explosion. All large scale explosions have resulted from chain reactions of this type. ‣ Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport. ‣ Build-up of electrostatic charge may be prevented by bonding and grounding. ‣ Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting. ‣ All movable parts coming in contact with this material should have a speed of less than 1-meter/sec. ‣ A sudden release of statically charged materials from storage or process equipment, particularly at elevated temperatures and/ or pressure, may result in ignition especially in the absence of an apparent ignition source.

Continued...

	▸ One important effect of the particulate nature of powders is that the surface area and surface structure (and often moisture content) can vary widely from sample to sample, depending of how the powder was manufactured and handled; this means that it is virtually impossible to use flammability data published in the literature for dusts (in contrast to that published for gases and vapours). ▸ Autoignition temperatures are often quoted for dust clouds (minimum ignition temperature (MIT)) and dust layers (layer ignition temperature (LIT)); LIT generally falls as the thickness of the layer increases. Combustion products include: ▸ carbon monoxide (CO) ▸ carbon dioxide (CO_2) nitrogen oxides (NOx) sulfur oxides (SOx) ▸ other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.
HAZCHEM	Not Applicable

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	▸ Remove all ignition sources. ▸ Clean up all spills immediately. ▸ Avoid contact with skin and eyes. ▸ Control personal contact with the substance, by using protective equipment. ▸ Use dry clean up procedures and avoid generating dust. ▸ Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. ▸ **CAUTION**: Advise personnel in area. ▸ Alert Emergency Services and tell them location and nature of hazard. ▸ Control personal contact by wearing protective clothing. ▸ Prevent, by any means available, spillage from entering drains or water courses. ▸ Recover product wherever possible. ▸ **IF DRY:** Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. **IF WET:** Vacuum/shovel up and place in labelled containers for disposal. ▸ **ALWAYS:** Wash area down with large amounts of water and prevent runoff into drains. ▸ If contamination of drains or waterways occurs, advise Emergency Services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	▸ Avoid skin contact, including inhalation. ▸ Wear protective clothing when risk of exposure occurs. ▸ Use in a well-ventilated area. ▸ Prevent concentration in hollows and sumps. ▸ **DO NOT** enter confined spaces until atmosphere has been checked. ▸ **DO NOT** allow material to come in direct contact with human skin or eyes. ▸ **DO NOT** allow material to come in contact with exposed food or food contact surfaces. ▸ Suitable PPE must be worn at all times. ▸ Avoid contact with incompatible materials. ▸ When handling, **DO NOT** eat, drink or smoke. ▸ Keep containers securely sealed when not in use. ▸ Avoid physical damage to containers. ▸ Always wash hands with soap and water after handling. ▸ Work clothes should be laundered separately. Launder contaminated clothing before re-use. ▸ Use good occupational work practice. ▸ Observe manufacturer's storage and handling recommendations contained within this SDS. ▸ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. ▸ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions) ▸ Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. ▸ Establish good housekeeping practices. ▸ Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds. ▸ Use continuous suction at points of dust generation to capture and minimise the accumulation of dusts. Particular attention should be given to overhead and hidden horizontal surfaces to minimise the probability of a "secondary" explosion. According to NFPA Standard 654, dust layers 1/32 in.(0.8 mm) thick can be sufficient to warrant immediate cleaning of the area. ▸ Do not use air hoses for cleaning. ▸ Minimise dry sweeping to avoid generation of dust clouds. Vacuum dust-accumulating surfaces and remove to a chemical disposal area. Vacuums with explosion-proof motors should be used. ▸ Control sources of static electricity. Dusts or their packages may accumulate static charges, and static discharge can be a source of ignition. ▸ Solids handling systems must be designed in accordance with applicable standards (e.g. NFPA including 654 and 77) and other national guidance. ▸ Do not empty directly into flammable solvents or in the presence of flammable vapors. ▸ The operator, the packaging container and all equipment must be grounded with electrical bonding and grounding systems. Plastic bags and plastics cannot be grounded, and antistatic bags do not completely protect against development of static charges. Empty containers may contain residual dust which has the potential to accumulate following settling. Such dusts may explode in the presence of an appropriate ignition source. ▸ Do NOT cut, drill, grind or weld such containers.

Continued...

	‣ In addition ensure such activity is not performed near full, partially empty or empty containers without appropriate workplace safety authorisation or permit.
Other information	‣ Store in original containers. ‣ Keep containers securely sealed. ‣ Store in a cool, dry area protected from environmental extremes. ‣ Store away from incompatible materials and foodstuff containers. ‣ Protect containers against physical damage and check regularly for leaks. ‣ Observe manufacturer's storage and handling recommendations contained within this SDS. For major quantities: ‣ Consider storage in bunded areas - ensure storage areas are isolated from sources of community water (including stormwater, ground water, lakes and streams}. ‣ Ensure that accidental discharge to air or water is the subject of a contingency disaster management plan; this may require consultation with local authorities.

Conditions for safe storage, including any incompatibilities

Suitable container	‣ Glass container is suitable for laboratory quantities ‣ Polyethylene or polypropylene container. ‣ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Ammonium sulfate: ‣ is strongly acid in aqueous solution ‣ reacts with caustics forming ammonia ‣ reacts violently with potassium chlorate ‣ when hot reacts with nitrates, nitrites, chlorates ‣ attacks metals ‣ is incompatible with sulfuric acid, aliphatic amines, alkanolamines, amides, organic anhydrides, isocyanates, vinyl acetate, alkylene oxides, epichlorohydrin, potassium plus ammonium nitrate, sodium-potassium powder plus ammonium nitrate ‣ mixtures with sodium hypochlorite form unstable, explosive nitrogen trichloride ‣ Avoid strong bases. ‣ Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

MATERIAL DATA

It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.
At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.
NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.
Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.
OSHA (USA) concluded that exposure to sensory irritants can:
‣ cause inflammation
‣ cause increased susceptibility to other irritants and infectious agents
‣ lead to permanent injury or dysfunction
‣ permit greater absorption of hazardous substances and
‣ acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

32maa

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. ‣ Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction. ‣ Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace. ‣ If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of: (a): particle dust respirators, if necessary, combined with an absorption cartridge; (b): filter respirators with absorption cartridge or canister of the right type; (c): fresh-air hoods or masks ‣ Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding. ‣ Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant. Type of Contaminant: | Air Speed:

Continued...

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 ft/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500-2000 ft/min)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 ft/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment



Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.[AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

Skin protection

See Hand protection below

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:
· frequency and duration of contact,
· chemical resistance of glove material,
· glove thickness and
· dexterity
Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).
· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
· Contaminated gloves should be replaced.
As defined in ASTM F-739-96 in any application, gloves are rated as:
· Excellent when breakthrough time > 480 min
· Good when breakthrough time > 20 min
· Fair when breakthrough time < 20 min
· Poor when glove material degrades
For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.
It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential
Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- polychloroprene.
- nitrile rubber.
- butyl rubber.
- fluorocaoutchouc.
- polyvinyl chloride.

Gloves should be examined for wear and/ or degradation constantly.

Body protection

See Other protection below

Other protection

- Overalls.
- P.V.C apron.
- Barrier cream.
- Skin cleansing cream.

Continued...

	‣ Eye wash unit.

Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	P1 Air-line*	- -	PAPR-P1 -
up to 50 x ES	Air-line**	P2	PAPR-P2
up to 100 x ES	-	P3	-
		Air-line*	-
100+ x ES	-	Air-line**	PAPR-P3

* - Negative pressure demand ** - Continuous flow
A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

· Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
· The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
· Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
· Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
· Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
· Use approved positive flow mask if significant quantities of dust becomes airborne.
· Try to avoid creating dust conditions.
Class P2 particulate filters are used for protection against mechanically and thermally generated particulates or both.
P2 is a respiratory filter rating under various international standards, Filters at least 94% of airborne particles
Suitable for:
· Relatively small particles generated by mechanical processes eg. grinding, cutting, sanding, drilling, sawing.
· Sub-micron thermally generated particles e.g. welding fumes, fertilizer and bushfire smoke.
· Biologically active airborne particles under specified infection control applications e.g. viruses, bacteria, COVID-19, SARS

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Off white crystalline granules.

Physical state	Divided Solid	**Relative density (Water = 1)**	1.77
Odour	Ammonia - like	**Partition coefficient n-octanol / water**	Not Available
Odour threshold	Not Available	**Auto-ignition temperature (°C)**	Not Available
pH (as supplied)	4-6	**Decomposition temperature (°C)**	Not Available
Melting point / freezing point (°C)	280	**Viscosity (mm2/s)**	Not Available
Initial boiling point and boiling range (°C)	Not Available	**Molecular weight (g/mol)**	Not Applicable
Flash point (°C)	Not Available	**Taste**	Not Available
Evaporation rate	Not Available	**Explosive properties**	Not Available
Flammability	Not Applicable	**Oxidising properties**	Not Available
Upper Explosive Limit (%)	Not Available	**Surface Tension (dyn/cm or mN/m)**	Not Applicable
Lower Explosive Limit (%)	Not Available	**Volatile Component (%vol)**	Not Available
Vapour pressure (kPa)	Not Available	**Gas group**	Not Available
Solubility in water	Miscible	**pH as a solution (1%)**	Not Available
Vapour density (Air = 1)	Not Available	**VOC g/L**	Not Available
Heat of Combustion (kJ/g)	Not Available	**Ignition Distance (cm)**	Not Available
Flame Height (cm)	Not Available	**Flame Duration (s)**	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	**Enclosed Space Ignition Deflagration Density (g/m3)**	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	‣ Unstable in the presence of incompatible materials. ‣ Product is considered stable. ‣ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7

Continued...

Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

a) Acute Toxicity	There is sufficient evidence to classify this material as acutely toxic.
b) Skin Irritation/Corrosion	There is sufficient evidence to classify this material as skin corrosive or irritating.
c) Serious Eye Damage/Irritation	There is sufficient evidence to classify this material as eye damaging or irritating
d) Respiratory or Skin sensitisation	Based on available data, the classification criteria are not met.
e) Mutagenicity	Based on available data, the classification criteria are not met.
f) Carcinogenicity	Based on available data, the classification criteria are not met.
g) Reproductivity	Based on available data, the classification criteria are not met.
h) STOT - Single Exposure	There is sufficient evidence to classify this material as toxic to specific organs through single exposure
i) STOT - Repeated Exposure	Based on available data, the classification criteria are not met.
j) Aspiration Hazard	Based on available data, the classification criteria are not met.

Inhaled	Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled. If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Sulfate salts are poorly absorbed from the gastro-intestinal tract but because of osmotic activity are able to draw water from the lumen to produce diarrhoea (purging). Sulfate ion usually has little toxicological potential. Human metabolism allows detoxification of ammonia, however toxic effects appear if this mechanism is overwhelmed by other than small doses. Ingestion of ammonium salts may produce local irritation, nausea, vomiting and diarrhoea. Very large doses of ammonium salts may produce a drop in blood pressure, collapse, central nervous system disorders, spasms, narcosis, respiratory paralysis and haemolysis. Large doses of ammonium salts may be sufficiently absorbed to produce diuresis and systemic ammonia poisoning. Such poisonings have been described after parenteral administration of the salts and produce flaccidity of facial muscles, tremor, generalised discomfort, anxiety and impairment of motor performance, recognition and of critical flicker fusion. Such a clinical picture resembles that found in terminal liver failure - elevated levels of ammonia are found regularly in advanced liver disease.
Skin Contact	Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.
Chronic	Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. Limited evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a significant number of individuals at a greater frequency than would be expected from the response of a normal population. Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching. Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking. Long term exposure to high dust concentrations may cause changes in lung function (i.e. pneumoconiosis) caused by particles less than 0.5 micron penetrating and remaining in the lung. A prime symptom is breathlessness. Lung shadows show on X-ray. Levels above 10 ug/m3 of suspended inorganic sulfates in the air may cause an excess risk of asthmatic attacks in susceptible persons

Apparent Spray Grade Ammonium Sulphate 980 Herbicide Adjuvant	**TOXICITY**	**IRRITATION**
	Not Available	Not Available

Continued...

ammonium sulfate	**TOXICITY** / **IRRITATION** dermal (rat) LD50: >2000 mg/kg[1] / Eye: no adverse effect observed (not irritating)[1] Oral (Rat) LD50: 2840 mg/kg[2] / Skin (Mammal - species unspecified): 50%/5D Skin: no adverse effect observed (not irritating)[1]
Legend:	***1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances***

Apparent Spray Grade Ammonium Sulphate 980 Herbicide Adjuvant & AMMONIUM SULFATE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. for ammonium sulfate As ammonium sulfate dissociates in biological systems studies with other ammonium and sulfate salts can be used to cover these endpoints: A screening study according to OECD TG 422 with ammonium phosphate as analogue substance, which forms ammonium ions in aqueous solutions is available. Fully valid fertility studies with analogue compounds containing sulfate ions are however lacking. Two limited studies with sodium sulfate can be used for assessment of fertility and developmental toxicity, however, in none of these studies have the foetuses been examined histologically. There are no in vivo data on genotoxicity for ammonium sulfate. To bridge the data gap, data for ammonium chloride, which dissociates in aqueous media to form ammonium ions, as does ammonium sulfate, will be used. In aqueous media, ammonium sulfate dissociates in the ammonium and sulfate ions (NH4+, SO4 2-). These can be taken up into the body by the oral and respiratory routes. Absorbed ammonium is transported to the liver and there metabolised to urea and excreted via the kidneys. Ammonium is also an endogenous substance that serves a major role in the maintenance of the acid-base balance. Minor amounts of ammonium nitrogen are incorporated in the physiological N-pool. Sulfate is a normal intermediate in the metabolism of endogenous sulfur compounds, and is excreted unchanged or in conjugated form in urine. **Acute toxicity:** Ammonium sulfate is of relatively low acute toxicity (LD50, oral, rat: 2000 - 4250 mg/kg bw; LD50 dermal, rat/mouse > 2000 mg/kg bw; 8-h LC50, inhalation, rat > 1000 mg/m3). Clinical signs after oral exposure included staggering, prostration, apathy, and laboured and irregular breathing immediately after dosing at doses near to or exceeding the LD50 value. In humans, inhalation exposure to 0.1-0.5 mg ammonium sulfate/m3 aerosol for two to four hours produced no pulmonary effects. At 1 mg ammonium sulfate/m3 very slight pulmonary effects in the form of a decrease in expiratory flow, in pulmonary flow resistance and dynamic lung compliance were found in healthy volunteers after acute exposure. Neat ammonium sulfate was not irritating to the skin and eyes of rabbits. There is no data on sensitisation available. **Repeat dose toxicity:** A 14-day inhalation study on rats exposed to 300 mg/m3 , the only tested dose, did not report histopathological changes in the lower respiratory tract. As the respiratory tract is the target organ for inhalation exposure, the NOEL for toxicity to the lower respiratory tract is 300 mg/m3. The NOAEL after feeding diets containing ammonium sulfate for 13 weeks to rats was 886 mg/kg bw/day. The only toxicity sign found was diarrhea in male animals of the high-dose group (LOAEL: 1792 mg/kg bw/day). **Reproductive toxicity:** There are no valid studies available on the effects of ammonium sulfate on fertility and development. Based on data from a similar ammonium compound (diammonium phosphate), which has been tested up to 1500 mg/kg bw in a screening study according to OECD TG 422 in rats it can be concluded that ammonium ions up to the dose tested have no negative effects on fertility. In the 13-week feeding study of ammonium sulfate with rats, no histological changes of testes were observed up to 1792 mg/kg bw. The ovaries were not examined. Fully valid studies with sulfate on fertility are not available. In a limited study (pretreatment time short, low number of animals, no fertility indices measured) where female mice were treated with up to ca. 6550 mg sulfate/kg bw (as sodium sulfate) no effects on litter size were found. **Developmental toxicity:** Studies of developmental toxicity for ammonium sulfate are not available. In the screening study according to OECD TG 422 with up to 1500 mg diammonium phosphate/kg bw no effects on development have been detected in rats. In another limited screening study with exposure of mice to a single dose of 2800 mg sodium sulfate/kg bw no macroscopic effects or adverse effects on body weight gain have been detected in the pups. In both studies foetuses were not examined histopathologically **Genotoxicity:** Ammonium sulfate was not mutagenic in bacteria (Ames test) and yeasts with and without metabolic activation systems. It did not induce chromosomal aberrations in mammalian or human cell cultures. No in vivo genotoxicity tests are available. Based on the negative results from in vitro studies and the negative results in the micronucleus test in vivo with ammonium chloride a mutagenic activity of ammonium sulfate in vivo is unlikely. Similarly to other salts, high doses of ammonium sulfate may have the capability of tumour promotion in the rat stomach; it is, however, much less potent than sodium chloride when tested under identical conditions.

Acute Toxicity	✔	**Carcinogenicity**	✘
Skin Irritation/Corrosion	✔	**Reproductivity**	✘
Serious Eye Damage/Irritation	✔	**STOT - Single Exposure**	✔
Respiratory or Skin sensitisation	✘	**STOT - Repeated Exposure**	✘
Mutagenicity	✘	**Aspiration Hazard**	✘

Legend: ✘ ***– Data either not available or does not fill the criteria for classification***
✔ ***– Data available to make classification***

SECTION 12 Ecological information

Toxicity

Apparent Spray Grade Ammonium Sulphate 980 Herbicide Adjuvant	**Endpoint**	**Test Duration (hr)**	**Species**	**Value**	**Source**
	Not Available	Not Available	Not Available	Not Available	Not Available
ammonium sulfate	**Endpoint**	**Test Duration (hr)**	**Species**	**Value**	**Source**

Continued...

	EC50	48h	Crustacea	52-67mg/L	4
	LC50	96h	Fish	0.29-0.53mg/L	4
	NOEC(ECx)	216h	Fish	0.064mg/L	4

Legend: ***Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. US EPA, Ecotox database - Aquatic Toxicity Data 4. ECETOC Aquatic Hazard Assessment Data 5. NITE (Japan) - Bioconcentration Data 6. METI (Japan) - Bioconcentration Data 7. Vendor Data 8. User defined data***

Harmful to aquatic organisms.
for ammonium sulfate
Environmental fate:
Based on the physico-chemical properties of ammonium sulfate, water is expected to be the main target compartment. Although ammonium sulfate can be created in the atmosphere from ammonia and sulfur dioxide, this process is limited by atmospheric sulfur dioxide, not by ammonia, which has many natural sources. Particulate ammonium sulfate is removed from air by wet and dry deposition. There is no evidence for photodegradation of ammonium sulfate.
In unsterilised soil, ammonium sulfate is mineralised fairly rapidly, and subsequently nitrified. Nitrification and denitrification processes also occur naturally in streams and rivers, as well as in many secondary sewage treatment processes.
Based on the high water solubility and the ionic nature, ammonium sulfate is not expected to adsorb or bioaccumulate to a significant extent. However, mobility in soil may be reduced through ion-ion interactions.
Ecotoxicity:
Fish LC50 (96 h): Salmo gairdneri (juvenile) 173 mg/l
Fish NOEC (61 d): Oncorhyncus gorbuscha (alevins) 11 mg/l
Freshwater snail LC50 (24 h): Helisoma trivolysis (juvenile) 393 mg/l
Daphnia magna EC50 (96 h): >100 mg/l
Algae EC50 (18 d): Chlorella vulgaris 2700 mg/l (cell count)
The PNEC for the freshwater aquatic environment is based upon the lowest observed chronic toxicity result, the NOEC value of 11 mg/l ammonium sulfate for alevins of Oncorhynchus gorbuscha. An assessment factor of 100 is appropriate, leading to a freshwater aquatic PNEC of 0.11 mg/l. Supporting information is also available for three juvenile amphibian species. The most sensitive amphibians were 6 week-old Pseudacris regilla tadpoles, with a NOEC (10 d) of 82 mg/l ammonium sulfate.
Marine Environment
Marine acute data are available for fish, invertebrates and for phytoplankton, the latter being most sensitive. For Gymnodinium splendens and Gonyaulax polyedra , growth reduction was found at concentrations of 0.7 mg/l and above. No EC50 can be derived. For seawater invertebrates the lowest effect value was obtained for green mussel Perna viridis (96h-LC50 = 47.7 mg/l). For marine fish the lowest effect value was found for larvae of Sciaenops ocellatus with a LC50 (10 d) of 27 mg/l.
Microorganisms in sewage treatment:
Nitrification during sewage treatment plant operation involves both sensitive (no growth at 4700 but growth at 94 mg/l ammonium sulfate) and insensitive (growth at 4700 mg/l ammonium sulfate) strains of Nitrobacter spp. These results indicate that a NOEC for specific nitrifying bacteria will be greater than 94 mg/l.
In the terrestrial environment, the major effect of repeated ammonium sulfate application is a reduction in soil pH. The most toxic results for specific soil bacteria, for cyanobacteria in rice fields, show less than 50% reduction in nitrogen fixation at 330 kg/ha/yr in the absence of liming. Similar results are seen for plants, with 471 kg/ha/y for 6 years affecting drought resistance in Picea abies. The soil fauna is less sensitive, with both Collembolla and Cryptostigmata numbers increasing under 708 kg /ha/year ammonium sulfate application
for inorganic sulfates:
Environmental fate:
Data from tap water studies with human volunteers indicate that sulfates produce a laxative effect at concentrations of 1000 - 1200 mg/litre, but no increase in diarrhoea, dehydration or weight loss. The presence of sulfate in drinking-water can also result in a noticeable taste; the lowest taste threshold concentration for sulfate is approximately 250 mg/litre as the sodium salt. Sulfate may also contribute to the corrosion of distribution systems. No health-based guideline value for sulfate in drinking water is proposed. However, there is an increasing likelihood of complaints arising from a noticeable taste as concentrations in water increase above 500 mg/litre.
Sulfates are removed from the air by both dry and wet deposition processes. Wet deposition processes including rain-out (a process that occurs within the clouds) and washout (removal by precipitation below the clouds) contribute to the removal of sulfate from the atmosphere.
In soil, the inorganic sulfates can adsorb to soil particles or leach into surface water and groundwater. Sulfates can be taken up by plants and be incorporated into the parenchyma of the plant.
Sulfate in water can also be reduced by sulfate bacteria (***Thiobacilli***) which use them as a source of energy.
In anaerobic environments sulfate is biologically reduced to (hydrogen) sulfide by sulfate reducing bacteria, or incorporated into living organisms as source of sulfur, and thereby included in the sulfur cycle. Sodium sulfate is not reactive in aqueous solution at room temperature. Sodium sulfate will completely dissolve, ionise and distribute across the entire planetary "aquasphere". Some sulfates may eventually be deposited, the majority of sulfates participate in the sulfur cycle in which natural and industrial sodium sulfate are not distinguishable
The BCF of sodium sulfate is very low and therefore significant bioconcentration is not expected. Sodium and sulfate ions are essential to all living organisms and their intracellular and extracellular concentrations are actively regulated. However some plants (e.g. corn and ***Kochia Scoparia***), are capable of accumulating sulfate to concentrations that are potentially toxic to ruminants.
Ecotoxicity:
For sulfate in general:
Fish LC50: toxic from 7000 mg/l
Bacteria: toxic from 2500 mg/l
Algae were shown to be the most sensitive to sodium sulfate; EC50 120 h = 1,900 mg/l. For invertebrates ***(Daphnia magna)*** the EC50 48 h = 4,580 mg/l and fish appeared to be the least sensitive with a LC50 96h = 7,960 mg/l for ***Pimephales promelas***. Activated sludge showed a very low sensitivity to sodium sulfate. There was no effect up to 8 g/l.
Sodium sulfate is not very toxic to terrestrial plants. ***Picea banksiana*** was the most sensitive species, an effect was seen at 1.4 g/l. Sediment dwelling organisms were not very sensitive either, with an LC50 96h = 660 mg/l for ***Trycorythus sp***. Overall it can be concluded that sodium sulfate has no acute adverse effect on aquatic and sediment dwelling organisms. Toxicity to terrestrial plants is also low.
No data were found for long term toxicity. The acute studies all show a toxicity of sodium sulfate higher than 100 mg/l, no bioaccumulation is expected,
For Ammonia:
Atmospheric Fate: Ammonia reacts rapidly with available acids (mainly sulfuric, nitric, and sometimes hydrochloric acid) to form the corresponding salts. Ammonia is persistent in the air.
Aquatic Fate: Biodegrades rapidly to nitrate, producing a high oxygen demand. Non-persistent in water (half-life 2 days).
Ecotoxicity: Moderately toxic to fish under normal temperature and pH conditions and harmful to aquatic life at low concentrations. Does not concentrate in food chain.
DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ammonium sulfate	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
ammonium sulfate	LOW (LogKOW = 0.48)

Mobility in soil

Ingredient	Mobility
ammonium sulfate	LOW (Log KOC = 6.124)

Continued...

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	▸ Containers may still present a chemical hazard/ danger when empty. ▸ Return to supplier for reuse/ recycling if possible. Otherwise: ▸ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. ▸ Where possible retain label warnings and SDS and observe all notices pertaining to the product. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: ▸ Reduction ▸ Reuse ▸ Recycling ▸ Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted. ▸ **DO NOT** allow wash water from cleaning or process equipment to enter drains. ▸ It may be necessary to collect all wash water for treatment before disposal. ▸ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▸ Where in doubt contact the responsible authority.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
ammonium sulfate	Not Applicable

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
ammonium sulfate	Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

ammonium sulfate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)
FEI Equine Prohibited Substances List - Banned Substances
FEI Equine Prohibited Substances List (EPSL)

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (ammonium sulfate)
China - IECSC	Yes
Colombia - Colombia National Industrial Chemicals Inventory	No (ammonium sulfate)
Europe - EINEC / ELINCS / NLP	Yes

Continued...

National Inventory	Status
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	Yes
Legend:	***Yes = All CAS declared ingredients are on the inventory*** ***No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.***

SECTION 16 Other information

Revision Date	06/11/2026
Initial Date	06/11/2026

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC—TWA: Permissible Concentration-Time Weighted Average
- PC—STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit。
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code

- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.
Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.
TEL (+61 3) 9572 4700.

end of SDS