POISON KEEP OUT OF REACH OF CHILDREN READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Apparent-



Ramjet 75-D

HERBICIDE

ACTIVE CONSTITUENT:

300g/L 2,4-D present as the TRIISOPROPANOLAMINE SALT 75g/L PICLORAM present as the TRIISOPROPANOLAMINE SALT

GROUP



HERBICIDE

THIS IS A PHENOXY HERBICIDE THAT CAN CAUSE SEVERE DAMAGE TO NATIVE VEGETATION AND SUSCEPTIBLE CROPS SUCH AS COTTON, GRAPES, TOMATOES, OILSEED CROPS AND ORNAMENTALS.

Additional instructions for use of this product under Permit 87174:

AIRR APPARENT PTY LTD

15/16 Princes Street, Newport NSW 2106
P 03 5820 8400 | E enquiries@apparentag.com.au | www.apparentag.com.au

п

blank page

INSTRUCTIONS FOR PERSONS WHO POSSESS, HAVE CUSTODY OF OR USE THE CANCELLED OR SUSPENDED PRODUCT

A person who possesses, has custody of or uses a product bearing a cancelled or suspended label referred to in the above Tables 1 and 2 in accordance with the instructions contained in this notice, is taken to have been issued with a permit under section 45B(3) of the Agvet Code to possess, have custody of or use the product bearing the cancelled or suspended label in accordance with those instructions.

The instructions in this notice form part of the amended label instructions for a 2,4-D product bearing a cancelled or suspended label.

Use of a 2,4-D product bearing a cancelled or suspended label may only take place in accordance with:

- 1. the instructions appearing on the cancelled or suspended label attached to the product; and
- 2. the general instructions in this notice; and
- 3. the instructions in this notice which correspond to the product's specific group.

POSSESSION OR CUSTODY

A person may possess the product bearing the cancelled or suspended label referred to in the above tables in accordance with its label instructions for 12 months from the Date of Cancellation or Date of Suspension.

USE, SUPPLY OR OTHERWISE DEAL WITH

A person may use the product bearing the cancelled or suspended label referred to in Table 1 or 2 according to its label instructions, including any conditions relating to shelf life or expiry date, and the instructions in this notice, for 12 months from the Date of Cancellation or Date of Suspension.

INSTRUCTIONS FOR USE

Use of a 2,4-D product bearing a suspended or cancelled label may only take place in accordance with:

- the instructions appearing on the suspended or cancelled label attached to the product; and
- · the instructions in this notice.

In the event of any inconsistency between the instructions appearing on the suspended or cancelled label for a product and the instructions in this notice, the instructions in this notice are to prevail to the extent of the inconsistency.

These instructions do not authorise any person to use a 2.4-D product bearing a suspended

- or cancelled label:in any situation; or
- · at any time; or

in any state or territory;

if the person would not be authorised to use the product in that situation, at that time, or in that state or territory under the instructions appearing on the suspended or cancelled label attached to the container for the product.

INSTRUCTIONS FOR SUPPLY

A person may supply, or cause to be supplied, at wholesale or retail level the product bearing a cancelled or suspended label referred to in Tables 1 and 2, for 12 months from the Date of Cancellation or Date of Suspension.

The supply of the product bearing a cancelled or suspended label may only take place in accordance with the following conditions (new supply instructions):

 For products manufactured prior to 1 October 2020: at the time of supply, the supplier must provide to the person taking possession or custody of the product bearing a suspended or cancelled label a copy of these instructions.

0r

For products manufactured on or after 1 October 2020: either a copy of these instructions or the current approved label must be securely affixed to each container of the product.

WARNING—CONTRAVENTIONS

After the day that is 12 months from the Date of Cancellation or Date of Suspension it will be an offence against the Agvet Code to have possession or custody of the products bearing the cancelled or suspended labels with the intention to supply, or to supply the cancelled or suspended products bearing the cancelled or suspended labels. It is an offence to possess, have custody of, use, or otherwise deal with the products bearing the cancelled or suspended labels listed in Tables 1 and 2 in a manner that contravenes the above instructions.

CONSEQUENCES OF FAILING TO COMPLY WITH INSTRUCTIONS

Failing to comply with the instructions in this notice or the instructions detailed in the Gazette amounts to an offence under section 45C(5) of the Agvet Code and may result in civil penalty proceedings under section 45C(7) of the Agvet Code.

If you have any questions, please contact Chemical Review by phone (02 6770 2400) or email (chemicalreview@apvma.gov.au). A summary of the decision is also available on the APVMA website.

DIRECTIONS FOR USE:

GENERAL INSTRUCTIONS FOR ALL 2,4-D PRODUCTS BEARING A SUSPENDED OR CANCELLED LABEL

This is a phenoxy herbicide that can cause severe damage to native vegetation and susceptible crops such as cotton, grapes, tomatoes, oilseed crops and ornamentals,

Restraints

DO NOT apply in a manner that may cause an unacceptable impact to native vegetation, agricultural crops, landscaped gardens and aquaculture production, or cause contamination of plant or livestock commodities, outside the application site from spray drift. The buffer zones in the relevant buffer zone tables below provide guidance but may not be sufficient in all situations. Wherever possible, correctly use application equipment designed to reduce

spray drift and apply when the wind direction is away from these sensitive areas. **DO NOT** allow bystanders to come into contact with the spray cloud.

DO NOT apply unless the wind speed is between 3 and 15 kilometres per hour at the application site during the time of application.

DO NOT apply if there are surface temperature inversion conditions present at the application site during the time of application. These conditions exist most evenings one to two hours before sunset and persist until one to two hours after sunrise.

Recognising a surface temperature inversion

A surface temperature inversion is likely to be present if:

- mist, fog, dew or a frost have occurred
- smoke or dust hangs in the air and moves sideways, just above the ground surface
- cumulus clouds that have built up during the day collapse towards evening
- wind speed is constantly less than 11 km/hr in the evening and overnight
- cool off-slope breezes develop during the evening and overnight
- · distant sounds become clearer and easier to hear
- aromas become more distinct during the evening than during the day.

Spray timing

- Spray during the day wherever possible. Vertical mixing of the air makes surface temperature inversions unlikely and will reduce the risk of drift caused by surface temperature inversions.
- There is a very low risk of surface temperature inversion when there is continuous overcast weather, with low and heavy cloud and/or wind speed remains above 11km/h for the whole period between sunset and sunrise.
- A lack of suitable weather conditions for spraying over extended periods is not an excuse for spraying in unsuitable conditions.

DO NOT apply if crop or weeds are stressed due to dry or excessively moist conditions. **DO NOT** apply with spray droplets smaller than VERY COARSE spray droplets according to the ASAE S572.1 definition for standard nozzles.

DO NOT use if rain is likely within 6 hours.

Monitoring and record keeping

Users of this product **MUST** make an accurate written record of the details of each spray application within 24 hours following application and KEEP this record for a minimum of 2 years. The spray application details that must be recorded are:

- 1. date of use with start and finish times of application;
- $2. \ \ the \ specific \ location \ which \ must \ include \ address \ and \ paddock/s \ sprayed;$
- 3. Product trade name (full name) of the product being used;
- rate of application which must include the amount of product used per hectare and number of hectares applied to;
- 5. situation, crop or commodity to which the chemical was applied;
- 6. wind speed and direction during application;
- 7. air temperature and relative humidity during application;
- 8. nozzle brand, model, size, type, and spray system pressure measured during application;
- 9. height of spay boom from ground;
- name and contact details of person applying this product (Additional record keeping and/ or details may be required by the state or territory where this product is used).

Watch for changes in weather conditions. Stop spraying immediately if a surface temperature inversion occurs or if spraying conditions become unsuitable for any other reason.

Advisory for boom sprayer use in cereals, fallow and pasture 1 October to 15 April

- Use in cereals, fallow and pastures during the period 3 October to 15 April, it is advised to:-
- Use nozzles that produce extremely coarse (xc) to ultra coarse (uc) droplets.
- Use higher water rates per ha, to give better efficacy.
- Use slower application speeds to allow operators to lower boom heights.
- Increasing droplet size and water rates while reducing application speed will assist in mitigating off target inversion drift during summer spraying. Extremely coarse droplets will produce <3% driftable droplets.

BOOM SPRAYERS (GROUND APPLICATION)

DO NOT apply by a boom sprayer unless the following requirements are met:

- spray droplets not smaller than a VERY COARSE (VC) spray droplet size category (minimum XC between 3 October and 15 April – advisory).
- boom heights 0.5 metres or lower above the target canopy (the higher of either the crop canopy or the targeted weeds)

- minimum distances between the application site and downwind sensitive aquatic and wetland areas including aquacultural ponds, surface streams and rivers (see Aquatic 'Downwind mandatory no-spray zone' section of the following table titled 'Buffer zones for boom sprayers') are observed.
- minimum distances between the application site and downwind sensitive crops, gardens, landscaping vegetation, protected native vegetation or protected animal habitat (see Terrestrial 'Downwind mandatory no-spray zone' section of the following table titled 'Buffer zones for boom sprayers') are observed. The buffer zones provide guidance but may not always be completely protective of all agricultural crops.

BUFFER ZONES FOR BOOM SPRAYERS

Group 4 (300 g 2 4-D + 75 g nicloram/L as the triisopropanolamine salt

Group 4 (300 g 2,4-D + 75 g picloram/L as the triisopropanolamine salt):						
Application rate (/ha)	Downwind manda	tory no spray zone				
	Aquatic	Terrestrial				
Dryland cropping: winter cereals and fallows						
Up to 1.1 L (325 g ae/ha)	0 metres	0 metres				
Dryland cropping: summer cereal	S					
Up to 500 mL + 280 mL 24D	0 metres	0 metres				
Amine 625 (325 g ae/ha)						
Tropical & subtropical uses: Suga	ircane					
Up to 0.7 L + 1 L 24D Amine	10 metres	10 metres				
500 (710 g ae/ha)						
Up to 1.5 L + 1 L 24D Amine	15 metres	15 metres				
500 (950 g ae/ha)						
Up to 2.4 L (1080 g ae/ha)	20 metres	20 metres				
Pasture						
Up to 15 L (4500 g ae/ha)	70 metres	65 metres				

DIRECTIONS FOR USE FOR AERIAL APPLICATION

To enable aerial application of 2,4-D products the following instructions are provided:

 Nozzle selection to achieve mandatory VERY COARSE or Larger Droplet Size Categories for aerial application.

Important information

These instructions inform users of 2,4-D products how to lawfully comply with the requirement of a VERY COARSE or larger spray droplet size category for aerial spray application.

Complying with the requirement to use a specific droplet size category means using the correct nozzle that will deliver that droplet size category under the spray operation conditions being used. Only the following specific methods can be used for choosing the correct nozzle. Use one of the methods specified in these instructions to select a correct nozzle to deliver a VERY COARSE or larger droplet size category for aerial application.

Instructions for Fixed-Wing Aerial Application – for VERY COARSE droplet size or larger categories

Instructions in this section apply to fixed-wing aerial application of products for which a label or a permit Spray Drift Restraint requires VERY COARSE spray droplet category. Nozzle choices must be made using Option 1 or 2 below.

Mandatory Instructions for Fixed-Wing Aerial Applications Option 1

For up to a maximum aircraft speed of 120 knots and a VERY COARSE droplet size category, USE ONLY narrow angle flat fan nozzles with spray angle less than or equal to 25, orifice size 20 or greater and oriented straight back to the flight direction. USE ONLY a spray system pressure greater than or equal to 4 bar.

Option 2

USE ONLY nozzles rated by the APVMA Approved AAAA Nozzle Calculator or the USDA-ARS Aerial Spray Nozzle Models as VERY COARSE to comply with a product label's requirement for a VERY COARSE spray droplet size category. When using the AAAA Nozzle Calculator or the USDA-ARS Aerial Spray Nozzle Models, aerial applicators must also follow the additional instructions below in (a), (b) and (c).

- (a) Aerial applicators must only use the droplet size category given in the nozzle calculator at the DV(0.1) position to identify a nozzle to comply with the required spray droplet category. The categories shown at the DV(0.5) and the DV(0.9) positions in the calculator must not be used for making a nozzle selection.
- (b) Aerial applicators must not apply at airspeeds greater than that speed used to select the nozzle. A nozzle identified as VERY COARSE can also be used at slower airspeeds provided that the nozzle angle and system pressure are kept the same.
- (c) When a particular pesticide product is chosen within the nozzle calculator as one of the conditions set to select a nozzle, then aerial applicators must use that specific pesticide product with that nozzle.

Note – contact the Aerial Application Association of Australia (aaaa.org.au) for information on how to obtain access to the APVMA Approved AAAA Nozzle Calculator; the USDA-ARS Aerial Spray Nozzle Models can be downloaded from their website (ars.usda.gov/plains-area/college-station-tx/southern-plains-agricultural-research-center/aerial-application-technology-research/docs/a-models).

Instructions for Helicopter Aerial Application – for VERY COARSE droplet size or larger categories

Instructions in this section apply to helicopter application of products where a label or a permit Spray Drift Restraint requires VERY COARSE spray droplet category.

Nozzle choices must be made using Option 1 or 2 below.

Mandatory Instructions for helicopter Aerial Applications

Option 1

For helicopter applications requiring a VERY COARSE spray droplet size category, USE ONLY nozzles selected with the methods previously specified for fixed-wing aircraft in Section 1.

Option 2

When using Accu-Flo nozzles (Bishop Equipment Mfg Inc), USE ONLY nozzles rated according to the manufacturer's instructions to select the correct nozzle to apply a VERY COARSE or an EXTREMELY COARSE droplet size category to satisfy the label requirement for one of those specific droplet size categories.

Examples of nozzles and settings that can achieve VERY COARSE or Larger Droplet

	es using Sect					
For flying spo						
Nozzle	Fan Angle	Deflector		Orientation	Pressure	Category
model	(deg)		Size	to airstream	(psi)	
				(deg)		
CP11TT	-		10	0	40 or higher	Very
straight			15		50 or higher	Coarse
stream			20		60 or higher	
CP09	-	0	0.078	0	70 or higher	
			0.125		90 or higher	
				craft and Helicop		
Nozzle	Fan Angle	Deflector	Orifice	Orientation	Pressure	Category
model	(deg)		Size	to airstream	(psi)	
CP09	-	0	0.078	0	30 or higher	Very
			0.125		35 or higher	Coarse
CP11TT	-		10 or	0	40 or higher	Extremely
straight			larger			Coarse
stream			-			
For flying spe	eeds up to 60	knots (Heli	copters):			
Nozzle	Fan Angle	Deflector	Orifice	Orientation	Pressure	Category
model	(deg)		Size	to airstream	(psi)	
CP09	-	30	0.078	0	30 or higher	Very
						Coarse
			0.125		30 or higher	Extremely
					-	Coarse
CP03	0		0.062 or	0	30	Extremely
			larger			Coarse
STANDARD	40	-	6 or	0	30 or higher	Very
	40	-	6 or larger	0	30 or higher	Very Coarse
STANDARD Flat Fan STANDARD	40	-		0	30 or higher 30 or higher	Coarse
Flat Fan		-	larger		_	

larger

Coarse

FF40

AERIAL APPLICATION

DO NOT apply by aerial application unless the following requirements are met:

- . spray droplets not smaller than a VERY COARSE (VC) spray droplet size category
- release heights 5 metres or lower above the target canopy
- minimum distances between the application site and downwind sensitive aquatic and wetland areas including aquacultural ponds, surface streams and rivers (see Aquatic 'Downwind mandatory no-spray zone' section of the following table titled 'Buffer zones for aircraft) are observed.
- minimum distances between the application site and downwind sensitive crops, gardens, landscaping vegetation, protected native vegetation or protected animal habitat (see Terrestrial 'Downwind mandatory no-spray zone' section of the following table titled 'Buffer zones for aircraft) are observed. The buffer zones provide guidance but may not always be completely protective of all agricultural crops.

BUFFER ZONES FOR AIRCRAFT FOR SUGARCANE BASED ON LOW APPLICATION RATE: (product groups 2, 3, 4, 5, 6, 7, 8a, 8b, 9a, 9b, 10, 11, 12, 13, 16, 14a, 14b): 3 metre release height or lower above the target canopy

Application	Spray droplet	Downwind mandatory no spray zone				
rate (/ha)	size category	Fixed	Fixed wing		opter	
, ,		Aquatic	Terrestrial	Aquatic	Terrestrial	
Tropical & subtro	pical uses: Sugarcane					
Up to 1080 g	Very Coarse or	95 metres	90 metres	90 metres	85 metres	
ae/ha	larger					
	Extremely Coarse	70 metres	70 metres	70 metres	65 metres	
	or larger					
Up to 1250 g	Very Coarse or	110 metres	100 metres	95 metres	95 metres	
ae/ha	larger					
	Extremely Coarse	80 metres	75 metres	75 metres	70 metres	
	or larner					

BUFFER ZONE FOR AIRCRAFT: 3m release height or lower above the target canopy.

Group 4 (300 g 2,4-D + 75 g picloram/L as the triisopropanolamine salt): 3 metre release height or lower above the target canony

Application rate	Dov	vnwind manda	tory no spray z	one
(/ha)	Fixed wing Heli			opter
` '	Aquatic	Terrestrial	Aquatic	Terrestrial
Dryland cropping: winter	cereals and fallo	WS		
Up to 1.0 L (325 g	40 metres	40 metres	40 metres	40 metres
ae/ha)				
Dryland cropping: summ	er cereals			
Up to 500 mL + 280 mL	40 metres	40 metres	40 metres	40 metres
24D Amine 625 (325				
g ae/ha)				
Tropical & subtropical us	es: Sugarcane			
Up to 0.7 L + 1.0 L	70 metres	70 metres	70 metres	65 metres
2,4-D 500 g/L (710 g				
ae/ha)				
Up to 1.5 L + 1.0 L	85 metres	85 metres	80 metres	80 metres
2,4-D 500 g/L (950 g				
ae/ha)				

BUFFER ZONES FOR AIRCRAFT: 5 metre release height or lower above the target canopy

Group 4 (300 g 2,4-D + 75 g picloram/L as the triisopropanolamine salt): 5

metre release height or lower above the target canopy

metre release helynt or lower above the target callopy							
Application rate	Downwind mandatory no spray zone						
(/ha)	Fixed wing		Helic	copter			
	Aquatic	Terrestrial	Aquatic	Terrestrial			
Dryland cropping: winter	cereals and fallo	WS					
Up to 1.0 L (325 g	75 metres	70 metres	75 metres	70 metres			
ae/ha)							
Dryland cropping: summ	er cereals						
Up to 500 mL + 280 mL	75 metres	70 metres	75 metres	70 metres			
24D Amine 625 (325							
g ae/ha)							
Tropical & subtropical	uses: Sugarca	ne					
Up to 0.7 L + 1.0 L	130 metres	120 metres	110 metres	110 metres			
2,4-D 500 g/L (710 g							
ae/ha)							
Up to 1.5 L + 1.0 L	190 metres	350 metres	150 metres	220 metres			
2,4-D 500 g/L (950 g							
ae/ha)							

Pasture application by air - 5 m release height

Application rate 4500 g ae/ha, VERY COARSE droplet size, Aerial application (Group 4): 5 m release height or lower above target canopy

Aquatic protection

	Downwind no-spray zone			
Wind speed range at time of	Fixed Wing	Helicopter		
application				
From 3 to 7 kilometres per hour	750 metres	475 metres		
From 7 to 14 kilometres per hour	Not supported	525 metres		

Terrestrial protection (2,4-D salt formulations)

	Downwind no-spray zone				
Wind speed range at time of application	Fixed Wing	Helicopter			
From 3 to 7 kilometres per hour	725 metres	450 metres			
From 7 to 14 kilometres per hour	Not supported	500 metres			

Pasture application – 3 m release height

Application rate 4500 g ae/ha, VERY COARSE droplet size, Aerial application (Group 4): 3 m release height above target canopy

Aquatic protection

	Downwind no-spray zone			
Wind speed range at time of	Fixed Wing	Helicopter		
application				
From 3 to 7 kilometres per hour	475 metres	300 metres		
From 7 to 14 kilometres per hour	475 metres	300 metres		

Terrestrial protection (2,4-D salt formulations)

	Downwing n	o-spray zone	
Wind speed range at time of	Fixed Wing	Helicopter	
application			
From 3 to 7 kilometres per hour	450 metres	275 metres	
From 7 to 14 kilometres per hour	450 metres	275 metres	

BUFFER ZONES FORESTRY USES FOR APPLICATION BY HELICOPTER AND ACCU-FLO NOZZLE, 0.020 ORIFICE OR LARGER (product groups 2, 3, 4, 5, 6, 7, 8a, 8b, 9a, 9b, 10, 11, 12, 13, 16, 14a, 14b)

DO NOT apply by fixed wing aircraft

DO NOT apply by helicopter unless the following requirements are met:

- Accu-FloTM nozzles with orifice size 0.020 or larger are used.
- · flying speed 102 km/hr (55 knots) or slower
- · release heights 15 metres or lower above the target canopy
- minimum distances between the application site and downwind sensitive aquatic and wetland areas including aquacultural ponds, surface streams and rivers (see Aquatic 'Downwind mandatory no-spray zone' section of the following table titled 'Buffer zones for aircraft) are observed.
- minimum distances between the application site and downwind sensitive crops, gardens, landscaping vegetation, protected native vegetation or protected animal habitat (see Terrestrial 'Downwind mandatory no-spray zone' section of the following table titled 'Buffer zones for aircraft) are observed. The buffer zones provide guidance but may not always be completely protective of all agricultural crops.

Application rate (/ha)	Wind speed range at time of application	Downwind mandatory no spra zone Helicopter			
		Aquatic	Terrestrial		
Release heights 15 metres or lower above the target canopy					
Up to 1000 g ae/ha	From 7 to 15 kilometres	75 metres	75 metres		
	per hour				
	From 3 to 7 kilometres	35 metres	35 metres		
	per hour				
Release heights 10 r	netres or lower above the targ	et canopy			
Up to 1000 g ae/ha	From 7 to 15 kilometres	45 metres	45 metres		
	per hour				
	From 3 to 7 kilometres	15 metres	15 metres		
	per hour				

VERTICAL SPRAYERS

DO NOT apply by a vertical sprayer unless the following requirements are met:

- · Spray is not directed above the target canopy
- The outside of the sprayer is turned off when turning at the end of rows and when spraying the outer row on each side of the application site.
- · For dilute water rates up to the maximum listed for each type of canopy specified, minimum distances between the application site and downwind sensitive areas (see 'Mandatory buffer zones' section of the following table titles 'Buffer zones for vertical sprayers') are observed.

Buffer zones for vertical sprayers

Group 15a (22.8 g 2,4-D								
Type of target canopy	Mandato	Mandatory buffer zones (distances given in metres)						
and dilute water rate	Bystander	Natural	Pollinator	Vegetation	Livestock			
	Areas	Aquatic	Areas	Areas	Areas			
		Areas						
2 metres tall and shorter,	Not	Not	Not	Not	Not			
maximum dilute water rate	Required	Required	Required	Required	Required			
of 1000 L/ha								
Taller than 2 metres		15 metres		15 metres				
(not fully-foliated),								
maximum dilute water rate								
of 4000 L/ha								
Taller than 2 metres (fully-		10 metres]	5 metres				
foliated), maximum dilute								
water rate of 4000 L/ha								

Group 15b (100 g 2,4-D/L as sodium salt)

Type of target canopy	Mandatory buffer zones (distances given in metres)					
and dilute water rate	Bystander	Natural	Pollinator	Vegetation	Livestock	
	Areas	Aquatic	Areas	Areas	Areas	
		Areas				
2 metres tall and shorter,	Not	Not	Not	Not	Not	
maximum dilute water rate	Required	Required	Required	Required	Required	
of 1000 L/ha						
Taller than 2 metres		15 metres		15 metres		
(not fully-foliated),						
maximum dilute water rate						
of 4000 L/ha						
Taller than 2 metres (fully-		10 metres]	5 metres		
foliated), maximum dilute						
water rate of 4000 L/ha						

blank page

17